



- NOTES:
1. M5 THREADED STUD. TORQUE NUTS TO 20 IN-LBS ± 2 IN-LBS.
 2. M6 THREADED STUD. TORQUE NUTS TO 34 IN-LBS ± 2 IN-LBS.
 - ▲ 3. MUST COMPLY WITH T.C.Co. GLOBAL SPEC 08.

ENGLISH

Q.A. SYMBOLS

- ★ = CATEGORY I
- ▲ = CATEGORY II
- = CATEGORY III
- = CATEGORY IV

REL		EC31636	CHANGE	DATE	*****	DWG NO.	SALES CONTROLLER				
<small>THIS DRAWING OR PRINT IS THE PROPERTY OF MASTERFLUX. IT IS NOT TO BE REPRODUCED, COPIED, OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM. WITHOUT THE WRITTEN CONSENT OF MASTERFLUX, THIS DRAWING OR PRINT IS TO BE KEPT CONFIDENTIAL AND NOT TO BE DISCLOSED OR MADE AVAILABLE TO ANY OTHER PARTY. ANY UNAUTHORIZED DISCLOSURE OR USE OF THIS DRAWING OR PRINT SHALL BE AT THE USER'S SOLE RISK AND WITHOUT LIABILITY TO MASTERFLUX. THIS DRAWING OR PRINT IS THE PROPERTY OF MASTERFLUX AND IS TO BE KEPT CONFIDENTIAL AND NOT TO BE DISCLOSED OR MADE AVAILABLE TO ANY OTHER PARTY. ANY UNAUTHORIZED DISCLOSURE OR USE OF THIS DRAWING OR PRINT SHALL BE AT THE USER'S SOLE RISK AND WITHOUT LIABILITY TO MASTERFLUX.</small>						DWG. NO.	SP 24MARIO	CK. ON FILE	APR. ON FILE	SCALE 1:1 & NOTED	THIS PRINT SUPERSEDES ALL PRINTS PRIOR TO
						MATERIAL	NOTED				
						DWG NO.	DGMX0042				